

## **UL CONSTRUCTION NO. 790**

CLASS A

Coated Steel and aluminum panel identified as "Snap-On Standing Seam", "High Snap-On Standing Seam", "Snap-On Batten", "Integral Batten", "Redi-Roof Batten", "Redi-Roof Standing Seam", "Snap-Clad", "Integral Standing Seam", "Tite-Loc" and "Tite-Loc Plus".

1	Deck:	NC No Line to the control of the con
	Incline: Barrier Board:	No Limitations 1/4 in. min G-P Gypsum DensDeck®
	Ply Sheet (optional):	Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified
	Try officer (optional).	prepared roofing accessory or WR Grace "Ice and Water Shield"
	Surfacing:	Steel or aluminum roofing panels, mechanically fastened
		Good of diameter of particle, moontained by factoring
2	Deck:	NC
	Incline:	No Limitations
	Barrier Board:	5/8 in min. plywood
	Ply Sheet (optional):	Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified
		prepared roofing accessory or WR Grace "Ice and Water Shield"
	Surfacing:	Steel roofing panels, mechanically fastened
3	Deck:	NC
	Incline:	No Limitations
	Barrier Board:	7/16 OBS or 5/8 in. plywood over polyisocyanurate insulation board or polyisocyanurate
		composite board, any thickness
	Ply Sheet (optional):	Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified
	0 ( ;	prepared roofing accessory or WR Grace "Ice and Water Shield"
	Surfacing:	Steel or aluminum roofing panels, mechanically fastened
4	Deck:	NC
·	Incline:	No Limitations
	Insulation:	Polyisocyanurate, glass fiber, perlite or wood fiber, any thickness
	Ply Sheet (optional):	Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified
	, (1 ,	prepared roofing accessory or WR Grace "Ice and Water Shield"
	Surfacing:	Steel or aluminum roofing panels, mechanically fastened
5	Deck:	NC
	Incline:	No Limitations
	Surfacing:	Steel roofing panels, mechanically attached to metal purlins
6	Deck:	C-15/32
J	Incline:	No Limitations
	Barrier Board:	1/4 in. min G-P Gypsum DensDeck® with all joints staggered a min of 6 in. from the
	barrior board.	plywood joints
	Ply Sheet (optional):	Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified
	, 5/1002 (00/10/10/).	prepared roofing accessory or WR Grace "Ice and Water Shield"
	Surfacing:	Steel or aluminum roofing panels mechanically fastened
	3	

## PETERSEN ALUMINUM CORPORATION