



TGFU.R14293 Roofing Systems

[Page Bottom](#)

Roofing Systems

[See General Information for Roofing Systems](#)

PETERSEN ALUMINUM CORP

R14293

1005 TONNE RD

ELK GROVE VILLAGE, IL 60007-4817 USA

Coated Steel and aluminum panel identified as "Snap-On Standing Seam", "High Snap-On Standing Seam", "Snap-On Batten", "Integral Batten", "Redi-Roof Batten", "Redi-Roof Standing Seam", "Snap-Clad", "Integral Standing Seam", "Tite-Loc", "Tite-Loc Plus", "Edge-Loc" and "PAC-150". One or more layers of GAF "VersaShield Underlayment", mechanically fastened or loose laid, may be used in lieu of the barrier board in all combustible Classifications.

OTHER SYSTEMS

Class A

1. **Deck:** NC

Incline: No Limitations

Barrier Board: — 1/4 in. min G-P Gypsum DensDeck® .

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or WR Grace "Ice and Water Shield" .

Surfacing: — Steel or aluminum roofing panels, mechanically fastened.

2. **Deck:** NC

Incline: No Limitations

Barrier Board: — 5/8 in. min plywood.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or WR Grace "Ice and Water Shield" .

Surfacing: — Steel roofing panels, mechanically fastened.

3. **Deck:** NC

Incline: No Limitations

Barrier Board: — 7/16 OBS or 5/8 in. plywood over polyisocyanurate insulation board or polyisocyanurate composite board, any thickness.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or WR Grace "Ice and Water Shield" .

Surfacing: — Steel or aluminum roofing panels, mechanically fastened.

4. **Deck:** NC

Incline: No Limitations

Insulation: — Polyisocyanurate, glass fiber, perlite or wood fiber, any thickness.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or WR Grace "Ice and Water Shield" .

Surfacing: — Steel or aluminum roofing panels, mechanically fastened.

5. **Deck:** NC

Incline: No Limitations

Surfacing: — Steel roofing panels mechanically attached to metal purlins.

6. **Deck:** C-15/32

Incline: No Limitations

Barrier Board: — 1/4 in. min G-P Gypsum DensDeck® with all joints staggered a min of 6 in. from the plywood joints.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or WR Grace "Ice and Water Shield" .

Surfacing: — Steel or aluminum roofing panels, mechanically fastened.

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".