



COPING TRANSITION MITERS

OUTSIDE MITER



- Standard Leg Lengths
 Custom Leg Lengths _____

INSIDE MITER



- Standard Leg Lengths
 Custom Leg Lengths _____

NOTES: -- Concealed splice plates are provided with factory applied dual non-curing sealant strips.

-- Unless otherwise noted, fabrication of miters and accessories are furnished standard utilizing a non-penetrating quicklock joint, then factory sealed watertight.

Fabrication will proceed only after receipt of signed print approval.

Print Approval:

Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Petersen Aluminum's printed instructions.

Approved by: _____

Date: _____

-- Welded Miters and Accessories

Check one Required (surcharge) Not applicable

MATERIAL:

- ___ 24 Ga. (.65 mm) Steel
 ___ .040" (1.01 mm) Alum. Color: _____
 ___ .050" (1.27 mm) Alum. Finish: _____
 ___ .063" (1.60 mm) Alum.
 ___ Other _____

QUANTITIES:

_____ Outside Miter(s) @ (_____°)
 _____ Inside Miter(s) @ (_____°)

- PAC-TITE Coping
 PAC-Continuous Cleat Coping
 Tapered Flat

PROJECT:

ARCHITECT:

ROOFING CONTRACTOR:

REPRESENTATIVE/DISTRIBUTOR:



Phone: 800-323-1960 Fax: 800-722-7150
 www.pac-clad.com
 e-mail: info@pac-clad.com

DATE: 10/15/10

DRN BY: JJC

CKD BY: SAK

SHT.# ___ OF ___

DWG# 41011-12587

A