



**KEYNOTES:**

- TRIM FASTENERS ARE SELF-DRILL PANCAKE HEAD AND MUST BE INSTALLED IN A STAGGERED PATTERN.
- CLIP AND FASTENER MATERIAL: GALVANIZED WHEN STEEL PANELS ARE UTILIZED; STAINLESS STEEL WHEN ALUMINUM PANELS ARE UTILIZED.
- CLIP FASTENERS MUST BE OF SUFFICIENT LENGTH TO PENETRATE PLYWOOD DECK BY 5/8" MINIMUM THREAD LENGTH.
- PLYWOOD DECK MUST BE A **MINIMUM OF 5/8" THICK.**
- ① "Z" COMPONENT
  - MINIMUM HEIGHT: 1/8" CLEARANCE OF PANEL RIB
  - FASTENED AS FOLLOWS: 12" & 16" PANELS (4 FASTENERS PER PANEL MINIMUM); 18" PANELS (6 FASTENERS PER PANEL MINIMUM)
  - FASTENING LEG: 1 1/4" MINIMUM TOP LEG: 1 1/2" MINIMUM
  - "Z" MUST BE CUT TO TIGHT FIT OF PANEL DIMENSION: **1/8" MAXIMUM GAP**
- ② SEALANT
  - TUBE OR TAPE SEALANT IS ACCEPTABLE BELOW THE "Z"
  - TUBE SEALANT PLACED AT BACKSIDE OF VERTICAL LEGS
  - 1" TAPE WIDTH OR 1/2" BEAD WIDTH PRIOR TO COMPRESSION
- ③ COUNTER FLASHING: HEMMED 1" AND FULLY ENGAGED TO "Z" CLOSURE.
- ④ FIRST PANEL CLIP TO BE LOCATED A **MAXIMUM OF 8" FROM "Z" COMPONENT.**

Job Name \_\_\_\_\_ Contractor \_\_\_\_\_

Date \_\_\_\_\_ Notes \_\_\_\_\_