



KEYNOTES:

- TRIM FASTENERS ARE SELF-DRILL PANCAKE HEAD AND MUST BE INSTALLED IN A STAGGERED PATTERN.
- CLIP AND FASTENER MATERIAL: GALVANIZED WHEN STEEL PANELS ARE UTILIZED; STAINLESS STEEL WHEN ALUMINUM PANELS ARE USED.
- CLIP FASTENERS MUST BE OF SUFFICIENT LENGTH TO PENETRATE PLYWOOD DECK BY 5/8" MINIMUM THREAD LENGTH.
- PLYWOOD DECK MUST BE A **MINIMUM OF 5/8" THICK.**
- ① EAVE FLASHING FASTENED AT 12" ON-CENTER MAXIMUM.
- ② FIRST PANEL CLIP TO BE LOCATED A **MAXIMUM OF 8" FROM EAVE.**
- ③ ROOF SIDE FLANGE SHOULD BE STRIPPED IN WITH APPROVED UNDERLAYMENT.
- ④ CLEAT: 24 GA. MINIMUM.
- ⑤ RETAINER CLIP: FASTENED TO SUPPORT PLATE AT 6" O.C. STAGGERED PATTERN.

Job Name _____ Contractor _____

Date _____ Notes _____