

NEGATIVE LOAD TABLE

(BASED ON 3 SPANS)

PAC PRECISION SERIES, HWP16 - 24 GA STEEL

Span (in feet)	AISI Design Load, 2.0 Safety Factor (psf)	USACE Design Load: 1.65 Safety Factor (psf)
1.00	-73.00	-88.48
1.25	-62.91	-76.25
1.50	-56.18	-68.09
1.75	-51.38	-62.27
2.00	-47.77	-57.90
2.25	-44.97	-54.50
2.50	-42.73	-51.79
2.75	-40.89	-49.56
3.00	-39.36	-47.70
3.25	-38.07	-46.14
3.50	-36.96	-44.79
3.75	-36.00	-43.63
4.00	-35.18	-42.64

NOTES

1. Results provided above based on 3-span conditions
2. Contact PAC local facility for 2-span or less conditions.
3. All tests performed by Farabaugh Engineering & Testing per ASTM E-330 Negative Uplift Testing
4. Results above provided in allowable Negative Wind Uplift per ASTM E-330 (psf)

PETERSEN ALUMINUM CORPORATION

PAC-CLAD.COM SALES@PETERSENMAIL.COM

HQ: 1005 Tonne Road
 Elk Grove Village, IL 60007
 P: 800-PAC-CLAD
 F: 800-722-7150

9060 Junction Drive
 Annapolis Junction, MD 20701
 P: 800-344-1400
 F: 301-953-7627

10551 PAC Road
 Tyler, TX 75707
 P: 800-441-8661
 F: 903-581-8592

102 Northpoint Parkway
 Acworth, GA 30102
 P: 800-272-4482
 F: 770-420-2533

1800 S. 7th Ave., Suite 130
 Phoenix, AZ 85007
 P: 833-750-1935
 F: 602-254-6504

1885 Station Parkway NW, Suite B
 Andover, MN 55304
 P: 877-571-2025
 F: 866-901-2935