



FASCIA INCLUDES 3 1/2"  
WIDE SPLICE PLATE AT JOINTS.

① STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE  
THICKER THAN .060".

② WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS  
AND ACCESSORIES ARE FURNISHED STANDARD.

**PAC-LOC FASCIA 2000 DIMENSIONS**

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-95S	9 3/4"	7 3/8"	4 NAILERS
<input type="checkbox"/> FA-110S	11 1/4"	8 7/8"	5 NAILERS
<input type="checkbox"/> FA-125S	12 3/4"	10 3/8"	6 NAILERS

ANSI/SPRI ES-1 DESIGN PRESSURE OF 110 psf

**AUTHORIZED SIGNATURE:**

APPROVED BY: \_\_\_\_\_

DATE: \_\_\_\_\_

**MATERIAL:**

\_\_\_ 24 GA. GALV. STEEL                      \_\_\_ .050" (1.27 mm) Alum.  
\_\_\_ .040" ALUMINUM                        \_\_\_ .063" (1.60 mm) Alum.  
\_\_\_ OTHER \_\_\_\_\_

COLOR: \_\_\_\_\_ FINISH: \_\_\_\_\_

**QUANTITIES:**

\_\_\_\_\_ LINEAL FEET 12'-0" LENGTHS  
\_\_\_\_\_ OUTSIDE MITER(S) @ (\_\_\_\_\_)°  
\_\_\_\_\_ INSIDE MITER(S) @ (\_\_\_\_\_)°    SPECIFY ACCESSORY TYPE:  
\_\_\_\_\_ RIGHT ENDCAP(S)                     WELDED ②  
\_\_\_\_\_ LEFT HANDCAP(S)                     STANDARD  
\_\_\_\_\_ RIGHT ENDWALL FLASHING(S)  
\_\_\_\_\_ LEFT ENDWALL FLASHING(S)  
\_\_\_\_\_ OVERFLOW SCUPPER(S) STYLE \_\_\_A\_\_\_B  
\_\_\_\_\_ SPILLOUT SCUPPER(S) STYLE \_\_\_A\_\_\_B  
\_\_\_\_\_ DOWNSPOUT SCUPPER(S) STYLE \_\_\_A\_\_\_B  
(\_\_\_\_X\_\_\_\_) SIZE    A: TAPERED 1 1/2" DROP  
   B: FLAT

PROJECT:

ARCHITECT:

ROOFING CONTRACTOR:

REPRESENTATIVE/DISTRIBUTOR:

PHONE: 800-323-1960 FAX: 800-722-7150  
WWW.PAC-CLAD.COM  
E-MAIL: INFO@PAC-CLAD.COM

DATE: 04/21/15  
DRN BY: JJC  
CKD BY: SAK

SHT.# \_\_\_ OF \_\_\_

DWG# 41010-21555

A