
# PAC-TITE WT EXTENDED FASCIA

## FULLY ADHERED OR MECHANICALLY ATTACHED SINGLE-PLY VERSION



#### SIZES

Face Heights
81⁄2", 10", 111⁄2", 13"



### **PRODUCT FEATURES**

- Unmatched uplift protection in roof edge applications
- Larger face sizes and heavier gauges for labor savings
- Concealed splice plates allow for cleaner design
- Non-penetrating design eliminates need for stripping in/heat welding
- Superior watertight integrity of the installation
- Extruded aluminum anchor bar securely terminates the membrane
- Extensively tested to exceed industry standards
- Pre-punched holes for precise fastener placement and quick installation
- Slotted holes allow for thermal movement
- Includes anchor bar EPDM splice plates and required fasteners
- Lifetime, 215 mph wind warranty available
- Wide variety of colors and finishes
- Convenient 12' Lengths
- Custom and radius capabilities available
- Reusable and recyclable for reinstallation

#### MATERIALS

- ▶ 15 Stocked PAC-CLAD Finishes (22 gauge steel )
- > 29 Stocked PAC-CLAD Finishes (.050 aluminum)
- ▶ 6 Stocked PAC-CLAD Finishes (.063 aluminum)
- Mill Finish Aluminum (.050 & .063 aluminum)
- Clear and Colored Anodized (.050 & .063 aluminum)

#### ACCESSORIES

- Miters (90 Degrees and Non-90 Degrees)
- Scuppers (Downspout, Spillout and Overflow)
- Drainage Components

#### TESTING

- ANSI/SPRI/FM 4435/ES-1 Standard to comply with the International Building Code
- Factory Mutual approved
- Miami-Dade Approved

#### WARRANTY

A Lifetime 215 mph warranty is available. It covers replacement or repair of any portion of the roof edge system that has failed due to a defect in the supplied materials. The warranty covers the roof edge for the lifetime of the roof on which it was originally installed.

