



KEYNOTES:

- TRIM AND SUPPORT PLATE FASTENERS ARE SELF-DRILL PANCAKE HEAD AND MUST BE INSTALLED IN A STAGGERED PATTERN.
 - CLIPS, FASTENERS, AND SUPPORT PLATE MATERIAL: GALVANIZED WHEN STEEL PANELS ARE UTILIZED; STAINLESS STEEL WHEN ALUMINUM PANELS ARE UTILIZED.
 - SUPPORT PLATE AND CLIP FASTENERS MUST BE OF SUFFICIENT LENGTH TO PENETRATE LOWEST FLUTE OF METAL DECK BY 5/8" MINIMUM THREAD LENGTH.
- ① RAKE FLASHING:
- PANEL LEG MUST BE FORMED TO WITHIN 1/8" OF J-CHANNEL WEB.
 - DECK SIDE LEG SHOULD BE A MINIMUM OF 3" LONG WITH FASTENER LOCATED 2" MAXIMUM FROM EDGE.
 - J-CHANNEL FORMED TO HEIGHT OF PANEL RIB.
- ② SEALANT CAN BE TUBE OR TAPE SEALANT AND MUST BE CONTINUOUS.
- ③ CLEAT: 24 GA. MINIMUM.
- ④ SUPPORT PLATE: 20 GA. MINIMUM (IF WOOD NAILERS ARE PRESENT, SUPPORT PLATE IS NOT NEEDED)

Job Name _____ Contractor _____

Date _____ Notes _____

PETERSEN ALUMINUM CORPORATION

PAC-CLAD.COM SALES@PETERSENMAIL.COM

HQ: 1005 Tonne Road
Elk Grove Village, IL 60007
P: 800-PAC-CLAD
F: 800-722-7150

9060 Junction Drive
Annapolis Junction, MD 20701
P: 800-344-1400
F: 301-953-7627

10551 PAC Road
Tyler, TX 75707
P: 800-441-8661
F: 903-581-8592

102 Northpoint Parkway
Acworth, GA 30102
P: 800-272-4482
F: 770-420-2533

1800 S. 7th Ave., Suite 130
Phoenix, AZ 85007
P: 833-750-1935
F: 602-254-6504

1885 Station Parkway NW, Suite B
Andover, MN 55304
P: 877-571-2025
F: 866-901-2935