



FLASHING COMPONENTS

**KEYNOTES:**

- TRIM AND SUPPORT PLATE FASTENERS ARE SELF-DRILL PANCAKE HEAD AND MUST BE INSTALLED IN A STAGGERED PATTERN.
  - CLIPS, FASTENERS, AND SUPPORT PLATE MATERIAL: GALVANIZED WHEN STEEL PANELS ARE UTILIZED; STAINLESS STEEL WHEN ALUMINUM PANELS ARE UTILIZED.
  - SUPPORT PLATE AND CLIP FASTENERS MUST BE OF SUFFICIENT LENGTH TO PENETRATE LOWEST FLUTE OF METAL DECK BY 5/8" MINIMUM THREAD LENGTH.
- ① RAKE FLASHING:
    - PANEL LEG MUST BE FORMED TO WITHIN 1/8" OF J-CHANNEL WEB.
    - DECK SIDE LEG SHOULD BE A MINIMUM OF 3" LONG WITH FASTENER LOCATED 2" MAXIMUM FROM EDGE.
    - J-CHANNEL FORMED TO HEIGHT OF PANEL RIB.
  - ② SEALANT CAN BE TUBE OR TAPE SEALANT AND MUST BE CONTINUOUS.
  - ③ SUPPORT PLATE: 20 GA. MINIMUM (IF WOOD NAILERS ARE PRESENT, SUPPORT PLATE IS NOT NEEDED)

Job Name \_\_\_\_\_ Contractor \_\_\_\_\_

Date \_\_\_\_\_ Notes \_\_\_\_\_

**PETERSEN ALUMINUM CORPORATION**

**PAC-CLAD.COM SALES@PETERSENMAIL.COM**

HQ: 1005 Tonne Road  
 Elk Grove Village, IL 60007  
 P: 800-PAC-CLAD  
 F: 800-722-7150

9060 Junction Drive  
 Annapolis Junction, MD 20701  
 P: 800-344-1400  
 F: 301-953-7627

10551 PAC Road  
 Tyler, TX 75707  
 P: 800-441-8661  
 F: 903-581-8592

102 Northpoint Parkway  
 Acworth, GA 30102  
 P: 800-272-4482  
 F: 770-420-2533

1800 S. 7th Ave., Suite 130  
 Phoenix, AZ 85007  
 P: 833-750-1935  
 F: 602-254-6504

1885 Station Parkway NW, Suite B  
 Andover, MN 55304  
 P: 877-571-2025  
 F: 866-901-2935