HIGH SNAP-ON STANDING SEAM PANEL


MATERIALS


.032 aluminum 24 gauge steel*

SPECS

10", 11", 12", 16" 1-1/2" High or 18" O.C.

UL-90







PRODUCT FEATURES

- Ideal for transition roofs
- Pencil ribs available
- ▶ 30-year non-prorated finish warranty
- Panel lengths up to 35'

MATERIAL

> 43 stocked colors (24 gauge steel)

- ▶ 36 stocked colors (.032 aluminum)
- ▶ Galvalume Plus available

UL CLASSIFICATION

- ▶ UL-580 Class 90 rated over solid substrate (steel only - up to 18" O.C.)
- ▶ UL-1897 wind uplift
- ▶ UL-790 Class A fire rated
- ▶ UL-263 fire resistance rated

ASTM TESTS

- ASTM E283/1680 tested
- ▶ ASTM E331/1646 tested

FLORIDA BUILDING PRODUCT APPROVALS

Please refer to pac-clad.com or your local factory for specific product approval numbers for Snap-On Panels.

* 11" and 18" 24 gauge steel High Snap-On Standing Seam panels are UL-90 Classified over solid substrate. See roof deck construction in Underwriter Laboratories roofing materials and systems directory.

A complete specification is available online at pac-clad.com.

