



Farabaugh Engineering and Testing Inc.

Project No. T206-21

Report Date: June 29, 2021

No. Pages: 18 pgs (Inclusive)

PERFORMANCE REPORT

ASTM E330 UNIFORM LOAD TEST

ON

MODULARAL METAL PANEL
30" WIDE COVERAGE X 0.080" ALUMINUM

FOR
PETERSEN ALUMINUM CORP.
10551 PAC RD.
TYLER, TX. 75707



Prepared by:

Paul G. Farabaugh

Approved by:

Daniel G. Farabaugh

DANIEL G. FARABAUGH, P.E.
255 Saunders Station Rd
Trafford, PA 15085
412-373-9238



DADE COUNTY
ACCREDITED
LABORATORY



AAMA
ACCREDITED
LABORATORY



TEXAS
ACCREDITED
LABORATORY



FLORIDA
ACCREDITED
LABORATORY
& QC ENTITY

STRUCTUAL TESTING

Purpose

The purpose of this test is to establish the structural loads on a 8'-0" wide x 8'-0" high wall system.

Test Date

5-28-21 thru 6-3-21

Test Specimen

Manufacturer: Petersen Aluminum Corp.
10551 Pac Rd.
Tyler, TX. 75707

Test Specimen: ModularAL Metal Panel 30" wide coverage x 0.080" aluminum

Mock-up Size: 96" wide X 96 high (nominal) consisting of 12 panels x 30" wide x various lengths of 0.050" thick aluminum panels.

Mock up -Installation

- The test setup consisted of a 96" wide x 96" high mock-up that used 6" x 16 ga. vertical channel studs spaced at 24" o.c that were attached to the top and bottom horizontal 16 ga. channel track.
- 5/8"thick Densglass Gypsum board was attached to the vertical stud supports using #6 x 1" lg. self -drilling fasteners spaced at 10" o.c.
- The panel support consisted of 16 ga. Zee horizontal supports attached thru the gypsum board and into 16 ga. vertical channel supports using #12 x 1-1/2" long wafer-head self -drilling screws. Additional vertical Zee supports were used at the panel clip locations.

- 1" foam board insulation was between all zee supports and entire mock-up was covered with Ice and Water Shield.
- A 16 ga. lower "J" channel was along the bottom and two sides of the mock-up. The "J" channel had predrilled holes thru the top leg and a #12 -14 x 1-1/2" long wafer-head self-drilling screws spaced at 22" o.c. secured the lower "J" channel thru the gypsum board and into the 16 ga. stud/channel track. The lower "J" channel secured the ends of the foam board and zee supports.
- A starter clip was attached to the Zee support using #12 x 1" lg. wafer-head, self-drilling screws. A minimum of two fasteners per starter clip or 12" o.c. max. spacing per clip based on length of clip.
- The starter panel engaged into a starter clip and was top-fastened with #12 x 1" lg. Stainless Steel Cap head w/EPDM Sealing washer fasteners at the predrilled holes spaced at 8" o.c. max. spacing.
- The vertical edge of the panel had two (2) clips to attach that edge to the 16 ga. vertical Zee supports using (2) #12 x 1" lg. wafer-head, self-drilling screws at each clip.
- A 0.08" aluminum "J" face trim was along the bottom and sides of the mock-up that sat on top of the lower "J" trim. The face trim was secured thru the lower 16 ga. trim and into stud supports with #14 x 3" lg. wafer-head, self-drilling screw spaced at 24" o.c..
- See installation details for location of fasteners at supports and attachment of each panel.

Test Procedure

The tests were conducted in accordance with the sections as shown in the following:

- ASTM E-330-02, "Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference "

ASTM E330 UNIFORM LOAD TEST

POSITIVE PRESSURE

Load Pressure (in-h20)	Load Pressure (psf)	Deflection #1 (in)	Deflection #2 (in)	Deflection #3 (in)
0	0.0	0.000	0.000	0.000
3	15.6	0.074	0.294	0.099
0	0.0	0.001	0.008	0.008
6	31.2	0.153	0.458	0.198
0	0.0	0.010	0.026	0.024
9	46.8	0.215	0.583	0.281
0	0.0	0.015	0.032	0.033
12	62.4	0.273	0.705	0.362
0	0.0	0.021	0.043	0.043
15	78.1	0.334	0.893	0.453
0	0.0	0.028	0.055	0.056
18	93.7	0.381	0.975	0.518
0	0.0	0.038	0.071	0.069
21	109.3	0.430	1.067	0.591
0	0.0	0.044	0.082	0.078
24	124.9	0.473	1.144	0.654
0	0.0	0.051	0.093	0.088
27	140.5	0.515	1.220	0.716
0	0.0	0.059	0.107	0.096
30	156.1	0.555	1.292	0.779
0	0.0	0.063	0.113	0.104
33	171.7	0.590	1.360	0.837
0	0.0	0.068	0.129	0.114
38.4	199.8	0.656	1.480	0.945
0	0.0	0.079	0.156	0.130

RESULTS

Upon completion of the testing at the positive pressures noted above there were no noticeable failures of the specimen


NEGATIVE PRESSURE

Load Pressure (in-h ₂ O)	Load Pressure (psf)	Deflection #1 (in)	Deflection #2 (in)	Deflection #3 (in)
0	0.0	0.000	0.000	0.000
2	10.4	0.052	0.182	0.048
0	0.0	0.006	0.007	0.006
4	20.8	0.130	0.329	0.129
0	0.0	0.021	0.029	0.022
6	31.2	0.209	0.454	0.215
0	0.0	0.039	0.052	0.041
8	41.6	0.299	0.587	0.317
0	0.0	0.061	0.082	0.064
10	52.0	0.407	0.734	0.443
0	0.0	0.082	0.103	0.096
12	62.4	0.501	0.850	0.525
0	0.0	0.126	0.159	0.142
14	72.9	0.599	0.977	0.634
0	0.0	0.159	0.202	0.183
16	83.3	0.699	1.103	0.748
0	0.0	0.190	0.237	0.225
18	93.7	0.820	1.258	0.884
0	0.0	0.237	0.291	0.278
20	104.1	0.919	1.386	1.004
0	0.0	0.279	0.343	0.332


RESULTS:

Maximum Test Load = 107.7 psf (Zee support fastener pulled out of 16 ga. metal stud supports)


STRUCTURAL TEST SETUP




PLAN VIEW





Project No. T206-21





Project No. T206-21














CUSTOMER	EMS-MO	CUSTOMER NO.	—	DIE NO.	052212	REV.
DESCRIPTION	1.250" X 1.250" H CHANNEL	PROPOSAL NO.	VB4A9308			

ACTUAL SIZE	
1.250	✓ P6F

ALUMINUM ASSOCIATION STANDARD TOLERANCES
APPLY UNLESS SPECIFIED OTHERWISE

UNSPECIFIED WALL THICKNESS	.093
UNSPECIFIED RADIUS	.016
EST AREA	.334 IN ²
EST WT.	.401 LBS/FT.
EST PER.	.7172 IN
OUT PER.	— IN
EXPD PER.	— IN
FACTOR	18
G.C.D.	1.755 IN

DIFF. RATING	—
DYN BY NEL	PRESS —
CKD BY	CAV. —
SCALE	3=1 BACK # —
CODE	— BOL # —
DATE	10-28-10 RATIO —
POCKET AREA	BLADE —
ALLUT	6063-15
DATE	SYM
REVISED	BY


sapa: SAPA EXTRUSIONS, INC.
2005 OLD OAKWOOD RD.
GAINESVILLE, GA. 30504
770-535-1349 800-544-3801
DIE NO. 052212

F. E. T. INC.	Review for general compliance
With last report AS NOTED ONLY	
BY:	P6F
PROJECT #	_____

PRODUCTION DRAWING	
11-12-10	RELEASER:
RELEASED DATE:	By: <i>Brucan Liang</i>
RELEASED BY:	DESTROY ALL PREVIOUS COPIES




ModularAL
Project




Enlarged Detail


ADDITIONAL SUPPORT AND TRIM EXTRUSIONS




0.080" ALUM.
STARTER CLIP



0.080" ALUM. "J" FACE TRIM
(TESTING PURPOSES ONLY)



16 GA. ZEE SUPPORT



16 GA. "J" LOWER TRIM
(TESTING PURPOSES ONLY)

Spectrochemical Laboratories-Material Evaluation, Inc.

155 Prominence Drive, New Kensington, PA. 15068

Phone: (724) 334-4140 Fax: (724) 334-4143

Project No. T206-21

Report of Tensile Testing

Client: Farabaugh Engineering & Testing (Ref. PO #: Verbal - P. Farabaugh)

PN#	Dimensions (in.)	Area (sq. - in.)	Yield Point (lb.)	Tensile Strength (lb.)	Yield Strength (psi.)	Tensile Strength (psi.)	Elongation (% in 2 in.)	Fracture Location
0.080" Alum.	0.4943 x 0.0787	0.0389	840	884	21600	22700	7.5	M/2 Break

Test Method: Q2300.04 rev.14 (ASTM A370-20, E8-21, or E646-16 : Yield by 0.2% offset, Elong, after fracture)

Equipment Used: Instron 5900R60HVL (s/n: 1602) w/ Extensometer (s/n: E93054)

Performed By: T. Ault

This test report shall not be reproduced except in full, without the written approval of the laboratory.

The recording of false, fictitious, or fraudulent statements or entries on this report may be punished as a felony under federal law.

Please send your comments and concerns to us at feedback@spectrochemline.com

For more information call: 724-334-4140

Respectfully submitted,



Todd A. Ault

Laboratory Manager