

# FM 4881 Approved (BAC-08)

## Engineering Technical Bulletin



### Fastening System C

#### PRODUCT

- ▶ **IWP Series:** Insulated Metal Wall Panel
- ▶ **Profiles:** Corr-Lok, Design-Lok, Mesa-Lok, Shadow-Lok
- ▶ **Thickness:** 4, 5 and 6 in. (102, 127 and 152 mm)
- ▶ **Core Material:** PIR
- ▶ **Width:** 24, 30, 36 and 42 in. (610, 762, 914 and 1067 mm)
- ▶ **Gauge:** min. 26-ga. (0.017 in, 0.43 mm) or heavier (interior and exterior facings)
- ▶ **Finish:** embossed or smooth

#### TEST PROTOCOL

- ▶ Approval Standard for Class 1 Exterior Wall Systems. Class Number 4881, November 2016

#### TEST LOCATION:

- ▶ FM Approvals, 743 Reynolds Road, West Glocester, RI 02814

#### REPORT NUMBER:

- ▶ PR451196

#### LISTING:

PRODUCT	WIDTH	PANEL THICKNESS	SECUREMENT	HAIL RESISTANCE RATING	WIND LOAD RATING & ZONE	MAX SUPPORT STEEL SPACING	MIN SUPPORT STEEL THICKNESS	MIN SUPPORT STEEL YIELD STRESS
PAC-CLAD INSULATED METAL PANELS (CORR-LOK, DESIGN-LOK, MESA-LOK, SHADOW-LOK)	42 IN. (1067MM)	2.0 - 6.0 IN. (51 - 152 MM)	FASTENING SYSTEM C	VERY SEVERE HAIL (VSH)	CLASS +130/-130 ZONE TC	48 IN. (1219 MM), 4'-0"	14 GA., 0.071 IN. (1.80 MM)	34 KSI (234 MPA)
					CLASS +80/-80 ZONE TC	60 IN. (1524 MM), 5'-0"		
					CLASS +65/-65 ZONE TC	72 IN. (1829 MM), 6'-0"		
					CLASS +55/-55 ZONE TC	84 IN. (2134 MM), 7'-0"		
					CLASS +50/-50 ZONE TC	96 IN. (2438 MM), 8'-0"		
					CLASS +45/-45 ZONE TC	108 IN. (2743 MM), 9'-0"		

**Table Notes:** Panels rated for Zone TC (Tropical Cyclone) may be used in Zones TC and NTC (Non-Tropical Cyclone). See Below for installation details for specific exterior wall panels.

PAC-CLAD Insulated Metal Panels (Corr-Lok, Design-Lok, Mesa-Lok, Shadow-Lok) minimum 0.017 (0.43) mm thick prefinished (optional) Galvalume® steel facers installed vertically or horizontally over steel structural members as indicated in the table above. Fastening System C - Panels are secured to minimum 14 ga. [0.071 in. (1.80 mm)] structural framing using (3) Triangle Fastener

Corporation BLAZER 3: 5/16-12 X 4" (9.5mm) hex head #3 drill point self-drilling fasteners per each BAC-08 clip within each panel side lap in each panel side joint to each supporting member.

**Green** - This product contains no CFC or HCFC.

**Green** - This product contains no urea-formaldehyde.



<b>Company Name:</b>	Petersen Aluminum Corporation
<b>Company Address:</b>	1005 Tonne Road, Elk Grove Village, IL 60007
<b>Company Website:</b>	www.pac-clad.com
<b>Green Product:</b>	Yes
<b>Application:</b>	Walls and Ceilings
<b>Class 1 Type/Rating:</b>	Inert-Faced with Combustible Core
<b>Height Restriction:</b>	No Height Restriction
<b>Listing Country:</b>	United States of America
<b>Certification Type:</b>	FM Approved
<b>Class of Work:</b>	4881-Exterior Wall Systems