

# Allowable Uniform Loads for Ridge-Lok

## Engineering Technical Bulletin



### PRODUCT

- ▶ **IRP Series:** Insulated Metal Roof Panel
- ▶ **Profiles:** Ridge-Lok
- ▶ **Width:** 42-inch or narrower
- ▶ **Thickness:** 2.5, 3, 4, 5 and 6-inch
- ▶ **Gauge:** 26-gauge or heavier (facer and liner)
- ▶ **Finish:** embossed or smooth

### ALLOWABLE UNIFORM LOADS (PSF)

PANEL THICKNESS (IN)	LOAD TYPE	SPAN (FT)										
		2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5
2.5	Positive	170.63	140.52	118.99	102.86	90.37	80.43	72.35	65.69	60.10	55.35	51.28
	Deflection*	132.45	108.50	91.28	78.29	68.15	60.03	53.38	47.84	43.16	39.16	35.70
	Negative (wind uplift)	78.05	69.38	63.19	58.55	53.65	48.29	43.90	40.24	37.14	34.49	32.19
3	Positive	201.27	165.96	140.67	121.71	106.99	95.27	85.73	77.83	71.21	65.58	60.75
	Deflection*	165.94	136.22	114.83	98.71	86.11	76.00	67.73	60.82	54.99	49.99	45.67
	Negative (wind uplift)	78.05	69.38	63.19	58.55	53.65	48.29	43.90	40.24	37.14	34.49	32.19
4	Positive	265.75	212.19	180.26	156.26	137.58	122.66	110.48	100.37	91.86	84.60	77.15
	Deflection*	215.85	177.85	150.52	129.90	113.77	100.83	90.20	81.33	73.81	67.37	61.79
	Negative (wind uplift)	78.05	69.38	63.19	58.55	53.65	48.29	43.90	40.24	37.14	34.49	32.19
5	Positive	303.53	251.26	213.79	185.61	163.65	146.07	131.70	119.74	109.65	101.03	93.60
	Deflection*	260.70	215.32	182.71	158.10	138.87	123.40	110.71	100.09	91.09	83.37	76.67
	Negative (wind uplift)	78.05	69.38	63.19	58.55	53.65	48.29	43.90	40.24	37.14	34.49	32.19
6	Positive	341.71	283.20	241.26	209.71	185.12	165.40	149.27	135.82	124.46	114.74	106.34
	Deflection*	300.47	248.58	211.32	183.22	161.25	143.60	129.09	116.96	106.66	97.82	90.14
	Negative (wind uplift)	78.05	69.38	63.19	58.55	53.65	48.29	43.90	40.24	37.14	34.49	32.19

### NOTES

1. Allowable loads were derived from test conducted in accordance with ASTM E1592 and ASTM E72.
2. All loads reflects standard fastening – RidgeLine clip with (2) ¼ - 14 self-drilling shoulder fasteners.
3. The above loads reflect attachment to 14-ga. steel supports. Attachment to other substrates must be designed separately.
4. Allowable loads assume a minimum bearing surface of 1.5".
5. Allowable loads are for uniform span lengths.
6. Allowable loads reflect a deflection limit of L/240.
7. The panel self-weight was not added or subtracted from the allowable loads.
8. Above load table does not consider thermal effects.

SUBJECT TO CHANGE WITHOUT NOTICE – Please visit our website for the most current information.

ETB-0014

PAC-CLAD® is a registered trademark of Petersen Aluminum Corporation. 11/24



PAC-CLAD.COM | 800 PAC CLAD