



INSULATED METAL PANEL WALL - VERTICAL - OPEN FRAMING DETAILS INSTALL DETAIL




THIS DETAIL DRAWING IS APPLICABLE TO ALL PAC-IMP SERIES WALL PANEL PROFILES

KEYNOTES:

- CLIP FASTENERS MUST PENETRATE TOP FACE OF WALL STUD SUBSTRATE BY 5/8" MINIMUM THREAD LENGTH
- CLIP SPACING AND TYPE VARIES BASED ON PROJECT SPECIFIC LOADS AND/OR LOCAL BUILDING CODES
- $\frac{3}{8}$ " UNIFORM BEAD OF NON-SKINNING BUTYL SEALANT MUST BE APPLIED IN THE EXTERIOR FEMALE GROOVE. APPLYING SEALANT IN THE INTERIOR GROOVE IS OPTIONAL DEPENDING ON VAPOR SEAL REQUIREMENTS.



SCALE: 3" = 1'-0"



EFFECTIVE DATE: 09-12-2024
SUBJECT TO CHANGE WITHOUT NOTICE

DISCLAIMER: DETAIL SHOWN FOR ILLUSTRATION PURPOSES ONLY. ACTUAL PROJECT DETAIL MAY VARY

PETERSEN ALUMINUM CORPORATION - PAC-CLAD.COM

SALES@PETERSENMAIL.COM

HQ: 1005 Tonne Road
Elk Grove Village, IL 60007
P: 800-PAC-CLAD
F: 800-722-7150

1255 S Caton Avenue, Suite B
Baltimore, MD 21227
P: 800-344-1400
F: 301-953-7627

10551 PAC Road
Tyler, TX 75707
P: 800-441-8661
F: 903-581-8592

102 Northpoint Parkway
Acworth, GA 30102
P: 800-272-4482
F: 770-420-2533

1800 S. 7th Ave., Suite 130
Phoenix, AZ 85007
P: 833-750-1935
F: 602-254-6504

9817 233rd Ave. E, Suite A
Bonney Lake, WA 98391
P: 253-501-2450

VS-0001