

ANSI/SPRI/FM 4435/ES-1 & FM Guide



FASCIA	FACE HEIGHT	COVER MATERIALS	PERIMETER FM RATING	CORNER FM RATING	ES-1 RATING	CLEAT LENGTHS	CLEAT MATERIAL	CLEAT TYPE	WIND WARRANTY	INSTALL METHOD
PAC-TITE Angular Fascia (Single-Ply)	4" 5.5"	24 ga., 22 ga. .040	1-270	1-225	275	12 ft.	Aluminum	Extruded Bar	Lifetime, 215 MPH	Snap-On
	7" 8.5"	24 ga., 22 ga. .040	1-150	1-120	155	12 ft.	Aluminum	Extruded Bar	Lifetime, 215 MPH	Snap-On
PAC-TITE Angular Fascia (BUR/MOD)	5.5"	24 ga., 22 ga. .040	1-270	1-225	275	12 ft.	Aluminum	Extruded Bar	Lifetime, 215 MPH	Snap-On
	7" 8.5"	24 ga., 22 ga. .040	1-150	1-120	155	12 ft.	Aluminum	Extruded Bar	Lifetime, 215 MPH	Snap-On
PAC-TITE WT Extended Fascia (Single-Ply)	8.5", 10" 11.5", 13"	22 ga. .050, .063	1-180	1-135	176	12 ft.	Aluminum Bar w/ 20 ga. Cleat	Extruded Bar w/Formed Cleat	Lifetime, 215 MPH	Snap-On
PAC-TITE WT Extended Fascia (BUR/MOD)	8.5", 10" 11.5", 13"	22 ga. .050, .063	1-180	1-135	176	12 ft.	Aluminum Bar w/ 20 ga. Cleat	Extruded Bar w/Formed Cleat	Lifetime, 215 MPH	Snap-On
PAC-TITE WT HG Fascia (Single-Ply)	4", 5.5" 7", 8.5" 10" (22 ga. only)	24 ga., 22 ga. .040	1-180	1-135	179	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
	4", 5.5", 7"	.050, .063	1-375	1-300	365	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
	8.5"	.050, .063	1-300	1-240	293	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
	10"	.050, .063	1-195	1-150	196	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
PAC-TITE WT HG Fascia (BUR/MOD)	5.5", 7"	24 ga. .040	1-180	1-135	179	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
	5.5", 7"	22 ga. .050, .063	1-375	1-300	365	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On

ANSI/SPRI/FM 4435/ES-1 & FM Guide



FASCIA	FACE HEIGHT	COVER MATERIALS	PERIMETER FM RATING	CORNER FM RATING	ES-1 RATING	CLEAT LENGTHS	CLEAT MATERIAL	CLEAT TYPE	WIND WARRANTY	INSTALL METHOD
PAC-TITE WT Canted Fascia (Galvanized Waterdam)	5.5", 7", 8.5" 10" (22 ga. only)	24 ga., 22 ga. .040	1-180	1-135	179	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
	8.5"	.050, .063	1-300	1-240	293	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
	10"	.050, .063	1-210	1-165	216	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
PAC-TITE WT Extended Fascia (Galvanized Waterdam)	9", 10.5" 12", 13.5"	22 ga. .050, .063	1-135	1-105	139	12 ft.	Aluminum Bar w/ 20 ga. Cleat	Extruded Bar w/Formed Cleat	Lifetime, 215 MPH	Snap-On
PAC-TITE Drip Edge (Flat or Pitched Flange)	3", 4.5" 6", 7.5"	24 ga., 22 ga. .040	1-90	1-75	98	12 ft.	Aluminum	Extruded Aluminum Bar	Lifetime, 215 MPH	Snap-On
PAC-LOC 2000 Fascia, Snap-on (Single-Ply)	5.25", 6.75" 8.25"	24 ga. .040	1-195	1-150	196	12 ft.	24 ga. Steel	Formed Canted Cleat	20 Year, 120 MPH	Snap-On
	5.25", 6.75" 8.25"	22 ga. .050, .063	1-210	1-165	216	12 ft.	24 ga. Steel	Formed Canted Cleat	20 Year, 120 MPH	Snap-On
	9.75", 11.25" 12.75"	22 ga. .050, .063	1-120	1-90	116	12 ft.	24 ga. Steel	Formed Canted Cleat	20 Year, 120 MPH	Snap-On
PAC-LOC 3000 Fascia, Snap-on (BUR/MOD)	5.25", 6.75" 8.25"	24 ga. .040	1-195	1-150	196	12 ft.	24 ga. Steel	Formed Canted Cleat	20 Year, 120 MPH	Snap-On
	5.25", 6.75" 8.25"	22 ga. .050, .063	1-210	1-165	216	12 ft.	24 ga. Steel	Formed Canted Cleat	20 Year, 120 MPH	Snap-On
	9.75", 11.25" 12.75"	22 ga. .050, .063	1-120	1-90	116	12 ft.	24 ga. Steel	Formed Canted Cleat	20 Year, 120 MPH	Snap-On

ANSI/SPRI/FM 4435/ES-1 & FM Guide

FASCIA	FACE HEIGHT	COVER MATERIALS	PERIMETER FM RATING	CORNER FM RATING	ES-1 RATING	CLEAT LENGTH	CLEAT MATERIAL	CLEAT TYPE	WIND WARRANTY	INSTALL METHOD
PAC Snap Edge Fascia (Single-Ply)	4", 5"	24 ga., 22 ga. .040	1-405	1-315	396	12 ft.	20 ga. Steel	Formed	20 Year, 120 MPH	Snap-On
	6.5", 8"	24 ga., 22 ga. .040	1-150	1-120	155	12 ft.	20 ga. Steel	Formed	20 Year, 120 MPH	Snap-On
PAC Snap Edge Fascia (BUR/MOD)	5"	24 ga., 22 ga. .040	1-420	1-345	419	12 ft.	20 ga. Steel	Formed	20 Year, 120 MPH	Snap-On
	6.5", 8"	24 ga., 22 ga. .040	1-180	1-135	179	12 ft.	20 ga. Steel	Formed	20 Year, 120 MPH	Snap-On
PAC Snap Edge Extended Fascia (Single-ply)	9.5", 11" 12.5"	22 ga. .050, .063	1-150	1-120	146	12 ft.	20 ga. Steel	Formed	20 Year, 120 MPH	Snap-On
PAC Snap Edge Extended Fascia (BUR/MOD)	9.5", 11" 12.5"	22 ga. .050, .063	1-150	1-120	146	12 ft.	20 ga. Steel	Formed	20 Year, 120 MPH	Snap-On

ANSI/SPRI/FM 4435/ES-1 & FM Guide

COPING	INSIDE FACE/ BACK	WALL WIDTH	OUTSIDE FACE/ FRONT	COVER MATERIAL	CLIP SPACING	CLIP MATERIAL	PERIMETER FM RATING	CORNER FM RATING	HORIZONTAL ES-1 RATING	VERTICAL ES-1 RATING	WIND WARRANTY	INSTALL METHOD
PAC-TITE Gold Coping (Tapered, Flat, Existing Slope)	4	10	6	22 ga. .050, .063	4' O.C.	16 ga. Steel	1-300	1-195	297	513	Lifetime, 215 MPH	Snap-on
	4	12	6	22 ga. .050, .063	4' O.C.	16 ga. Steel	1-240	1-150	233	403	Lifetime, 215 MPH	Snap-on
	4	16	6	22 ga. .050, .063	4' O.C.	16 ga. Steel	1-150	1-90	151	261	Lifetime, 215 MPH	Snap-on
	4	16	12	22 ga. .050, .063	4' O.C.	16 ga. Steel	1-150	1-90	151	261	Lifetime, 215 MPH	Snap-on
	4	24	6	22 ga. .050, .063	3' O.C.	16 ga. Steel	1-135	1-90	136	236	Lifetime, 215 MPH	Snap-on
	4	24	12	22 ga. .050, .063	3' O.C.	16 ga. Steel	1-105	1-75	110	191	Lifetime, 215 MPH	Snap-on
	4	32	6	22 ga. .050, .063	2' O.C.	16 ga. Steel	1-90	1-60	99	171	Lifetime, 215 MPH	Snap-on
	4	10	6	24 ga. .040	4' O.C.	16 ga. Steel	1-225	1-150	221	383	Lifetime, 215 MPH	Snap-on
	4	12	6	24 ga. .040	4' O.C.	16 ga. Steel	1-195	1-135	198	343	Lifetime, 215 MPH	Snap-on
	4	16	6	24 ga. .040	4' O.C.	16 ga. Steel	1-135	1-90	134	232	Lifetime, 215 MPH	Snap-on
	4	16	12	24 ga. .040	4' O.C.	16 ga. Steel	1-135	1-90	134	232	Lifetime, 215 MPH	Snap-on
	4	24	6	24 ga. .040	3' O.C.	16 ga. Steel	1-120	1-75	122	211	Lifetime, 215 MPH	Snap-on
	4	24	12	24 ga. .040	4' O.C.	16 ga. Steel	1-90	1-60	99	171	Lifetime, 215 MPH	Snap-on

ANSI/SPRI/FM 4435/ES-1 & FM Guide



COPING	INSIDE FACE/ BACK	WALL WIDTH	OUTSIDE FACE/ FRONT	COVER MATERIAL	CLIP SPACING	CLIP MATERIAL	PERIMETER FM RATING	CORNER FM RATING	HORIZONTAL ES-1 RATING	VERTICAL ES-1 RATING	WIND WARRANTY	INSTALL METHOD
PAC-TITE Coping (Tapered, Flat, Existing Slope)	4	8	6	22 ga. .050, .063	4' O.C.	20 ga. Steel	1-225	1-150	226	391	20 Year, 120 MPH	Snap-on
	4	12	6	22 ga. .050, .063	3' O.C.	20 ga. Steel	1-135	1-90	138	238	20 Year, 120 MPH	Snap-on
	4	14	6	22 ga. .050, .063	3' O.C.	20 ga. Steel	1-120	1-75	127	219	20 Year, 120 MPH	Snap-on
	4	16	6	22 ga. .050, .063	3' O.C.	20 ga. Steel	1-90	N/A	93	161	20 Year, 120 MPH	Snap-on
	4	8	6	24 ga. .040	4' O.C.	20 ga. Steel	1-165	1-105	164	283	20 Year, 120 MPH	Snap-on
	4	12	6	24 ga. .040	4' O.C.	20 ga. Steel	1-90	N/A	97	167	20 Year, 120 MPH	Snap-on
	4	12	6	24 ga. .040	3' O.C.	20 ga. Steel	1-120	1-75	123	213	20 Year, 120 MPH	Snap-on
	4	14	6	24 ga. .040	3' O.C.	20 ga. Steel	1-120	1-75	129	223	20 Year, 120 MPH	Snap-on

ANSI/SPRI/FM 4435/ES-1 & FM Guide

COPING	INSIDE FACE/ BACK	WALL WIDTH	OUTSIDE FACE/ FRONT	COVER MATERIAL	CLEAT LENGTH	CLEAT MATERIAL	PERIMETER FM RATING	CORNER FM RATING	HORIZONTAL ES-1 RATING	VERTICAL ES-1 RATING	WIND WARRANTY	INSTALL METHOD
PAC-Continuous Cleat Coping (Tapered, Flat, Existing Slope)	4	16	6	22 ga. .050, .063	12 ft.	20 ga.	1-240	1-165	244	422	20 Year, 120 MPH	Crimp-on
	4	16	12	22 ga. .050, .063	12 ft.	20 ga.	1-225	1-150	232	402	20 Year, 120 MPH	Crimp-on
	4	24	6	22 ga. .050, .063	12 ft.	20 ga.	1-135	1-90	131	226	20 Year, 120 MPH	Crimp-on
	4	24	12	22 ga. .050, .063	12 ft.	20 ga.	1-135	1-90	139	241	20 Year, 120 MPH	Crimp-on
	4	16	6	24 ga. .040	12 ft.	20 ga.	1-180	1-120	180	312	20 Year, 120 MPH	Crimp-on
	4	16	12	24 ga. .040	12 ft.	20 ga.	1-150	1-90	157	272	20 Year, 120 MPH	Crimp-on
	4	24	6	24 ga. .040	12 ft.	20 ga.	1-90	1-60	96	166	20 Year, 120 MPH	Crimp-on
	4	24	12	24 ga. .040	12 ft.	20 ga.	1-90	1-60	99	171	20 Year, 120 MPH	Crimp-on

GUTTER	FRONT & BOTTOM*	BACK*	FLANGE	GUTTER ATERIAL	INTERNAL BRACKET	LENGTH	GT-1 HORIZONTAL PRESSURE (PSF)	GT-1 VERTICAL PRESSURE (PSF)	GT-1 DOWNWARD PRESSURE (PSF)	GT-1 /FM HORIZONTAL PRESSURE (PSF)	GT-1 /FM VERTICAL PRESSURE (PSF)	GT-1 /FM DOWNWARD PRESSURE (PSF)	WIND WARRANTY
PAC-TITE WR Gutter Standard Design (Box, Offset, Chamfer)	5.25" to 7.75"	6.25" to 8.75"	0" to 4"	24 ga. .040	Extruded Alum. 24" O.C.	12 ft.	223	136	270	N/A	N/A	N/A	30 Year, 160 MPH
	5.25" to 7.75"	6.25" to 8.75"	0" to 4"	22 ga., .050, .063	Extruded Alum. 24" O.C.	12 ft.	223	108	270	N/A	N/A	N/A	30 Year, 160 MPH
PAC-TITE WR Gutter FM Design (Box, Offset, Chamfer)	5.25" to 7.75"	6.25" to 8.75"	0" to 4"	24 ga. 22 ga.	Extruded Alum. 18" O.C.	12 ft.	N/A	N/A	N/A	596	224	160	30 Year, 160 MPH
	5.25" to 7.75"	6.25" to 8.75"	0" to 4"	.040, .050, .063	Extruded Alum. 18" O.C.	12 ft.	N/A	N/A	N/A	309	201	240	30 Year, 160 MPH

*Available in 1/2" increments