

PAC T-250 STANDING SEAM PANEL

PANEL SECTION PROPERTIES – POSITIVE/NEGATIVE LOAD TABLES

SECTION PROPERTIES										ALLOWABLE UNIFORM LOADS, psf For various clip spacings (i.e. span values)						
Width, in.	Gauge	Yield, ksi	Weight, psf	Top in Compression			Bottom in Compression			Negative Load						
				I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft	I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft	2'	2.5'	3'	3.5'	4'	4.5'	5'
16	24	50	1.31	0.1490	0.1273	0.0823	0.0743	0.0960	0.0688	65.0	59.8	54.6	49.4	44.2	39.0	33.8
16	22	50	1.55	0.1920	0.1640	0.1059	0.0955	0.1235	0.0865	72.8	68.5	64.2	59.9	55.5	51.2	46.9
16	0.032"	25	0.451	0.2263	0.2263	0.1258	0.2263	0.2263	0.6471	65.0	58.9	52.9	46.8	40.7	34.7	28.6
16	0.040"	25	0.570	0.2797	0.2797	0.1548	0.2797	0.2797	0.7963	78.0	71.5	65.0	58.5	52.0	45.5	39.0

- 1a. Theoretical section properties for steel panels have been calculated per AISI S100 Specification for the Design of Cold-Formed Steel Structural Members.
- 1b. Theoretical section properties for aluminum panels have been calculated per the latest edition of the Aluminum Association Design Manual.
2. I_{xx} (eff) values are "effective" stiffness properties for positive (downward) load induced deflection determination.
3. S_{xx} values are to be used for flexural (bending) stress determination for downward (positive) pressure values only.
4. Charted Load/Span values are based on ASTM E1592-05 (2012) testing protocol.
5. Charted Load/Span values above are based on Allowable Stress Design (ASD).....Load Resistance Factor Design (LRFD) technique not recommended for charted values.
6. Charted Allowable Uniform Loads are based on the Ultimate Uniform Load (per ASTM E1592-05 testing) divided by a 2.00 Factor-of-Safety.
7. Charted Allowable Uniform Loads do not consider panel weight (Dead Load) or clip-to-substrate (structure) fastener connection strength.
8. Clip-to-substrate (structure) fastener evaluation must consider the Pry Effect applied to the fastener by the clip base and the analysis should be performed by a licensed structural engineer.
9. Panel tested over 16 ga. Steel supports.
10. Charted Allowable Uniform Loads do not consider deflection limits of panel.
11. Charted Allowable Uniform Loads cannot be increased by 1/3.
12. Panel tested using one (1) piece 6" long x 16 ga. sliding fit clip

SECTION PROPERTIES										ALLOWABLE LIVE LOADS, psf For various clip spacings (i.e. span values)											
Width, in.	Gauge	Yield, ksi	Weight, psf	Top in Compression			Bottom in Compression				Positive Load										
				I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft	I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft		1'	1.5'	2'	2.5'	3'	3.5'	4'	4.5'	5'	5.5'	6'
16	24	50	1.16	0.1490	0.1273	0.4973	0.0743	0.0960	0.0680	Stress	282.7	188.5	141.4	111.1	94.2	80.8	70.7	62.8	56.6	51.4	47.1
										Defl.	1720.0	764.4	430.0	275.2	191.1	140.4	107.5	84.9	68.8	56.9	47.8
16	22	50	1.25	0.1925	0.1644	0.1058	0.0955	0.1236	0.0865	Stress	399.1	266.1	199.6	159.6	133.0	114.0	99.8	88.7	79.8	71.5	60.1
										Defl.	2162.5	961.1	540.6	346.0	240.3	176.5	135.2	106.8	86.5	71.5	60.1
16	0.032"	25	0.451	0.2263	0.2263	0.1258	0.2263	0.2263	0.6471	Stress	50.9	30.8	17.3	11.1	7.7	5.7	4.3	3.4	2.8	2.3	1.9
										Defl.	69.3	30.8	17.3	11.1	7.7	5.7	4.3	3.4	2.8	2.3	1.9
16	0.040"	25	0.570	0.2797	0.2797	0.1548	0.2797	0.2797	0.7963	Stress	72.7	47.3	26.6	17.0	11.8	8.7	6.7	5.3	4.3	3.5	3.0
										Defl.	106.4	47.3	26.6	17.0	11.8	8.7	6.7	5.3	4.3	3.5	3.0

- 1a. Theoretical section properties for Steel panels have been calculated per 2020 AISI S100 North American Specification for the Design of Cold-Formed Steel Structural Member. I_{xx} and S_{xx} are effective section properties for deflection and bending.
- 1b. Theoretical section properties for Aluminum panels have been calculated per the 2020 edition of the Aluminum Association's Design Manual. I_{xx} and S_{xx} are effective section properties for deflection and bending.
- 2a. Allowable loads for Steel panels are calculated in accordance with 2020 AISI S100 specifications considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
- 2b. Allowable loads for Aluminum panels are calculated in accordance with the 2020 edition of the Aluminum Association's Design Manual considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
3. Allowable load does not address panel weight, fasteners, connection strength or support material.
4. Allowable load includes web crippling.
5. Load/Span values are based on theoretical computations and not load testing.
6. Deflection limit set to L/180.
7. Allowable loads do not include a 1/3 stress increase for wind.
8. The PAC T-250 Panel when installed as a three-span condition with spans of 5 ft. on-center for Steel and 3 ft. on-center for Aluminum are capable of withstanding the minimum uniform distributed load of 20 psf (0.958 kPa) noted in Table 1607.1 of the IBC and a minimum concentrated load of 300 lbf (1.33 kN).
9. When panels are installed over solid or closely fitted deck sheathing, the load capacity is limited to the structural capacity of the underlying sheathing.



Robert V. Nangia P.E.
7423 Hollow Ridge Drive
Houston, Texas 77095